

BUILT TO OUTLAST.

The SeedMaster Toolbar delivers long-lasting performance you can trust. Our bolt-together steel frame and the protection of our blast-to-bare metal powder coating makes our toolbars durable and easy to maintain. The SeedMaster Toolbar also comes in second-to-none with its dual-knife opener. Our opener delivers precise seed and fertilizer placement, fast uniform emergence and a field finish like no other.









STANDARD FEATURES

- Smart Openers: Lift and lower openers into the ground with an easy-to-use foot switch while also utilizing our ISO in-cab controller to adjust packing pressure
- Low Maintenance Opener Design: One of the lowest maintenance openers on the market designed with parts that are built to last
- Active Wing Brace: Counteracts opener draft force to distribute frame stress
- Lift Kit: Provides superior flotation when pulling through mud
- Matrix Wing Lock: Partially unfolds each wing for lower transport height, ensuring safe travel under power lines and overpasses
- Residue Deflectors: Reduces residue build-up on knives, ensures optimal product placement, and delivers exquisite field finish

- Blast to Bare Metal Paint Procedure: Flawless powder coat paint adhesion for an anti-corrosive finish that won't crack, chip, or peel
- Equal Length Distribution Kits: 2 1/2-Inch formed piping for equalized distribution
- 5-Year Frame Warranty

OPTIONS

- Tank Configurations: Can be configured to fit all SeedMaster products, including the UltraPro II On-Frame Tank, Nova Series II Air Cart or our Liquid Nova Fertilizer Tank
- High Flotation Rear Axle: Pairs well with the SeedMaster lift kit for flotation in muddy conditions
- Front Walkover Hitch: Quickly access either side of your toolbar

TOOLBAR CONFIGURATIONS

WORKING WIDTH		ROW SPACING		# OF ROWS	FRAME STYLE	APPROX TRANSPORT HEIGHT		APPROX TRANSPORT WIDTH		# OF ZONES
FT	М	IN	СМ			FT	М	FT	М	
40′	12.19	10"/12"	25.4/30.48	48/40	Compact M	16'2"	4.93	19'2"	5.84	8
50′	15.24	10"/12"	25.4/30.48	60/50	Compact M	14'1"	4.29	20'2"	5.94	8/10
60′	18.29	10"/12"/15"	25.4/30.48/38.1	72/60/48	Compact M	16'	4.88	20'8"	5.99	8/10
70′	21.35	10"/12"/15"	25.4/30.48/38.1	84/70/56	Compact M	18'2"	5.54	19'10"	5.66	8/10
80′	24.38	12"/15"	30.48/38.1	80/64	Compact M	20'2"	6.15	22′5″	6.53	8/10
80′	24.38	12"/15"	30.48/38.1	80/64	Wide M	18'2"	5.54	25'4"	7.72	8/10
90′	27.43	12"/15"	30.48/38.1	90/72	Wide M	21'	6.4	25′9″	7.85	10
100′	30.48	15"	38.1	80	Wide M	23'4"	7.11	26'1"	7.92	10

^{*} Other sizes are available on request. Customization conditions may apply.



^{*} For more transportation details, contact your local SeedMaster dealership.

^{*} Openers are factored in to all specifications.